USB / SD / microSD / CF Duplicator

## Flash Duplicator

Large number of ports — Support growing production.


Full Checking function — Quick find out defective flash.

High writing speed — Not shared while copying numerous flash.

Standalone — No PC, no risk of virus infection.

## www.EUROPALINK.net





labor cost down and remind productivity high. Europalink Flash duplicator is a professional, standalone and high speed equipment which can support hundreds of target for duplicating simultaneously and the rate of copying will not be affected (writing speed up to 33MB/Sec.). Furthermore, full checking functions like media check and capacity check can help you to ensure the quality of Flash efficiently.

Without PC or other install procedure required, U-Reach provides an easyoperated and reliable copy environment for users, no worry of complicated operation and risk of virus infection. This series of Flash duplicator coupled with high speed compare function to ensure copied data success and quick format capability to increase production efficiency.

The Flash duplicator series is an economical solution for data copy and distribution via flash drives. It embeds smart and beneficial functions and outstanding performance, reliability and quality that will save your time and

Europalink Flash duplicator series also suit for anyone to duplicate large/small numbers of USB flash drives for various applications such as government, education, house of worship, corporations (Marketing, Engineering, etc.) or individual home and office uses.



## Flash Duplicator Specification

Model		UB808	UB816	UB824	UB832	#×UB8XXX
		SD808	SD816	SD824	SD832	
		CF808	CF816	CF824	CF832	-
		MS808	MS816	MS824	MS832	1 4
Buffer Memory		256MB				
Target		1:7	1:15	1:23	1:31	1:40-XXX
Operation		Stand alone				
Support media		USB1.1 / USB2.0 / SD / SDHC / microSD / MMC / miniSD / CF				
Display		2*20 Monochrome LCD display				
Control Button		4 push buttons ( Forward , Backward, OK, Esc)				
LED		LED(Green/Red) on each slot				
Temperature	Working	5°C~45°C				
	Storage	-20°C~85°C				
Humidity	Working	20%-80%				
	Storage	5%-95%				
Power Supply		80 - 180W ; 100 - 240V				Above 300W 100/200V
Safety		FCC, CE ,RoHS				
System Dimension (L*W*H cm)- USB	Tower Case	28.5*19*16.5	41*17.5*28	41.5*19*35	40*22*45.5	6

\*The above information is for marketing reference only. The actual specification may subject to change without notice. \*\* The number of port and interface (USB/SD/microSD/CF) can be selected and increased based on customer requirement.